

# S750-S2-H60 Rotary Vane Medical Vacuum System

System is NFPA compliant and has modular construction and interconnecting piping.

## PUMP MODULE

Oil sealed rotary vane vacuum pump with NEMA motor. Each pump module is equipped with an inlet filter, check valve, pump isolation valve, and temperature switch.

## SYSTEM CONTROLS

The UL listed electrical control panel features a high-definition color touch screen that can be set up externally without the use of toggle switches. The panel displays multiple conditions, including pump running status, elapsed hours, vacuum level, and audio/visual alarms.

Standard features include lag alarm, automatic pump alternation, adjustable minimum run timer, adjustable vacuum settings, adjustable screen brightness, alarm history registry, and data logging. The panel has standard dry contacts and Modbus interface with building management systems. Ethernet and BACnet are available as options. The panel's maintenance menu includes service items and maintenance warnings, and it is programmed for both English and Spanish languages.

## VACUUM RECEIVER

Constructed to ASME standards and rated for full vacuum. Equipped with valved bypass, high visibility vacuum gauge, source isolation valve, and a manual drain valve. Mounting pads and flex connectors supplied for field installation.

## KEY OPTIONS

Variable Speed Drive Electrical Panel  
Configurable for Lab or Industrial Applications  
Gas Purge System for Lab use

<b>Configuration</b>	Duplex Stack Mount
<b>System Capacity*</b>	60.1 SCFM @ 19" Hg. 60 Hz. 50 SCFM @ 19" Hg. 50 Hz.
<b>Horsepower (Each Pump)</b>	7.5 HP
<b>Horsepower (Total System)</b>	15 HP
<b>Available Voltage</b>	208/230/460V 3PH 60 Hz. 380V 3 PH 50 Hz. Contact Factory for other voltages
<b>Full Load Amps 3 ph.</b>	208 Volts: 49.6 230 Volts: 45.1 380 Volts: 27.4 460 Volts: 22.6
<b>Tank Size</b>	60 gallon horizontal
<b>Bacterial Filter Bank (option)</b>	BOM-MED FB-2




Click here for pump specifications and industry-leading parts support

\*System capacity is stated with one pump in reserve per NFPA. Capacity based on operation at sea level. For higher altitude, contact factory for adjusted capacity.

SYSTEM MODEL NO.	PART NO.	HP EACH	SCHWAB/PM @ 17" Hg EACH	SCHWAB/PM @ 27" Hg EACH	DESIGN CAPACITY (@ 17" Hg EACH)	RECEIVER SIZE (GALLONS)	PUMP INLET NPT	ESTIMATED SYSTEM WEIGHT (LB)
S750B-S72	S750(C)-460-S2-H60	7.5	60.0 / 144.4	24.3 / 147.0	60.0	60	2"	1400

SPACE ALLOWANCE FOR MAINTENANCE = 3 FT. ON ALL SIDES. MORE SPACE IS REQUIRED FOR THE OPENING OF LARGER PANEL DOOR.

VOLTAGE	SYSTEM P/N	PUMP MODULE P/N	TRIP MODULE P/N
208-60-3	S750(C)-208-S2-H60	100-0205	214544
230-60-3	S750(C)-230-S2-H60	100-0205	214544
380-50-3	S750(C)-380-S2-H60	100-0205	214544



REV	QTY	PART NUMBER	DESCRIPTION	REF. MARK
1	2	30011	2" NPT ISOLATION VALVE	
2	4	34038	2" NPT ISOLATION VALVE	
3	4	A-1203 (P)	2 x 2" NPT W/PT	
4	12	A-1202 (P)	2" NPT COUPLER W/PT	
5	2	A-1208 (P)	2" Threaded Tee	
6	4	A-1210 (P)	2" Flange Elbow	
7	4	A-1212 (P)	UNION 2"	
8	1	8000001	ROTARY VANE VACUUM SYSTEM, 107.75 HP DUPLEX STACK MOUNT	

