

# SCH200-T2-H60 Claw Medical Vacuum System

System is NFPA compliant and has modular construction and interconnecting piping.

## **PUMP MODULE**

Oil-less rotary claw air cooled vacuum pump with 1750 RPM NEMA motor. Each pump module is equipped with an inlet filter, check valve, pump isolation valve, internal discharge silencer, and temperature switch.

#### SYSTEM CONTROLS

The UL listed electrical control panel features a high-definition color touch screen that can be set up externally without the use of toggle switches. The panel displays multiple conditions, including pump running status, elapsed hours, vacuum level, and audio/visual alarms.

Standard features include lag alarm, automatic pump alternation, adjustable minimum run timer, adjustable vacuum settings, adjustable screen brightness, alarm history registry, and data logging. The panel has standard dry contacts and Modbus interface with building management systems. Ethernet and BACnet are available as options. The panel's maintenance menu includes service items and maintenance warnings, and it is programmed for both English and Spanish languages.

## **VACUUM RECEIVER**

Constructed to ASME standards and rated for full vacuum. Equipped with valved bypass, high visibility vacuum gauge, source isolation valve, and a manual drain valve. Mounting pads and flex connectors supplied for field installation.

#### **KEY OPTIONS**

Variable Speed Drive Electrical Panel
O2 Assured Oil for gearbox
Configurable for Lab or Industrial Applications
Gas Purge System for Lab use

Configuration	Duplex Tank Mount
System Capacity*	11.7 SCFM @ 19" Hg. 60 Hz. 9.7 SCFM @ 19" Hg. 50 Hz.
Horsepower (Each Pump)	2 HP
Horsepower (Total System)	4 HP
Available Voltage	208/230/460V 3 PH 60 Hz. 380V 3 PH 50 Hz. Contact Factory for other voltages
Full Load Amps 3 ph.	208 Volts: 16.2 230 Volts: 14.7 380 Volts: 9.0 460 Volts: 7.4
Tank Size	60 gallon horizontal
Medical Filter Bank (standard))	BOM-MED-MVF15



Click here for pump specifications and industry-leading parts support.

<sup>\*</sup>System capacity is stated with one pump in reserve per NFPA. Capacity based on operation at sea level. For higher altitude, contact factory for adjusted capacity.





